

UniFi® SWITCH



UniFi Aggregation Switch

USW-Aggregation is a managed Layer 2 switch with eight 10G SFP+ ports, offering link aggregation for higher capacity and increased availability. USW-Aggregation features Layer 2 capabilities and supports high-bandwidth links, making it ideal for aggregation switching to any UniFi solution that deploys various interconnect topologies. Built-in 36W AC/DC power supply can support copper Ethernet UF-RJ45-10G modules (sold separately) in all eight ports.



Mechanical

Dimensions	442.4 x 120 x 43.7 mm (17.42 x 4.72 x 1.72")
Weight	Without Mount: 2.65 kg (5.84 lb) With Mount: 2.74 kg (6.04 lb)
Enclosure Material	SGCC Steel

Hardware

Total Non-Blocking Throughput	80 Gbps
Switching Capacity	160 Gbps
Forwarding Rate	119.04 Mpps
Max. Power Consumption	30W
Power Method	Universal AC Input: 100-240VAC, 50/60 Hz
Power Supply	AC/DC, Internal, 36W
Management Interface	Ethernet In-Band
Modes	SMB Layer 2 Gigabit Ethernet Switch
ESD/EMP Protection	Air: ± 16kV, Contact: ± 12kV
Operating Temperature	-5 to 40° C (23 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC



LEDs

System

(1) Bootup Animation: Bootup in Progress
Firmware Upgrade Icon: Firmware Upgrading
Steady White: Factory Defaults, Awaiting Adoption
Steady Blue: Device is Adopted

SFP+

White: 1/10G



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: www.ui.com/support/warranty
©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.

SICE DISTRIBUTORE UFFICIALE: www.sicetelecom.it